KAKKU MEDIUM DUTY (HOISTING APPLICATION) JOY STICK OPERATED MASTER CONTROLLERS SERIES MSCXK - 7400

SPECIAL FEATURES

- Available as single / dual axis controllers.
- Provided with Potentiometer, Double break contacts with high quality silver cadmium oxide contact tips having arc-retarding & anti-welding properties.
- Star wheel for positive notching at each step and pronounced notching at neutral, fatigue free step less operation
- KAKKU Joystick controllers are also noted for ease of assembly, dis-assembly & adjustments as well as free access to all the parts.
- Long life with reliable performance and trouble free operation.

APPLICATION

KAKKU Joystick Controllers Series MSCXK-7400 are used for control of electric drives of EOT cranes, hoists, transfer cars, Grabbuckets, unloaders, steel mills, conveyors and other heavy material handling equipment.

TECHNICAL DATA

Ambient Temperature : 55°C.

Mounting Arrangement : Suitable for foot/ wall mounting.
Housing : Metallic enclosure with sheet steel

cover.

: Upto 5 - 0 - 5

Enclosure Category : (Optional)

Terminals : Suitable for conductor size 2.5mm².

Operation : Stayput / Spring return.

Max. No. of operating

positions.

Max. No. of contacts per circuit (2 contacts / circuit)

(a) Single Master Controller: Upto 4(b) Dual axis: Upto 8

Potentiometer output : 0-10 V DC / 4-20 mA (OPTIONAL)
Mechanical Life : Approx 3 million operations

RATINGS

Rated Voltage AC : Upto 500V Continuous Current : 10A

OPTIONAL EXTRA


- Enclosure as per IP 41/54
- Deadman handle
- Deadman contact


SERIES MSCXK-7400

Dimensions (mm)

MODEL	LEVER	b	b1
MSCX7400	SHORT	288	181-186
	LONG	338	236-241

MODEL	DETAILS	a1	a2	C1	C2
MSCXK7402	WITH 2	51		52	
	CONTACTS				
MSCXK7403	WITH 2	65		65	
	CONTACTS &				
	SPRING				
	RETURN TO				
	ZERO				
MSCXK7404	WITH 4		90		90
	CONTACTS				
MSCXK7408	WITH 8		120		120
	CONTACTS				







Electronic & Power Control Co.

(AN ENTERPRISE OF KAKKU E & P CONTROL (P) LTD.)

1, Industrial Estate, Bhilai 490 026,
(Chhattisgarh) INDIA.



Tel : 91-788-2280610, 2286494 Fax : 91-788-2281797

E-mail : sales@kakkuindia.com Website : www.kakkuindia.com This document was created with Win2PDF available at http://www.win2pdf.com. The unregistered version of Win2PDF is for evaluation or non-commercial use only. This page will not be added after purchasing Win2PDF.